Accessories

Components & Sizes

	Components	Materials	Sizes
Nozzle Strainers	Optional strainer to fit BJ and CW nozzles. All strainers equipped with 316 stainless steel screens of various mesh sizes.	316 stainless steel	Mesh Sizes: 50 (S201) 100 (S202) 200 (S203) 400 (S204)
Reducing Bushings	BETE nozzles are often installed in pipe sizes larger than their con- nection. These bushings will adapt BETE nozzles to existing piping.	316 stainless steel nickel alloy C-276 nickel alloy 625 PVC PTFE	Bushing Sizes: 1/4 x 1/8 3/8 x 1/8, 1/4 1/2 x 1/8, 1/4, 3/8 1 x 1/4, 3/8, 1/2, 3/4 1-1/2 x 1/4, 1/2, 1 2 x 1/2, 1
Y-Type Line Strainers	BETE recommends the use of strainers to minimize clogging. The 1/4" and 3/8" strainers are equipped with 100-mesh screens, while 1/2" - 2" strainers come with 80-mesh screens. Screens with mesh sizes of 20, 24, 50 and 60 available on special order. Screens are easily removed for cleaning. 150 psi rating.	Bronze body with heavy-duty stainless steel wire mesh.	Strainer Sizes: 1/4, 3/8,1/2, 3/4, 1, 1-1/2, 2Mesh SizesScreen Opening1000.005"800.007"500.011"240.028"200.034"
Adapters and Couplings	Reducing couplings, socket adapters, elbows, and various other fittings are available to meet specific applications.	Wide range of materials available	Sizes available as required
Flanges	Alternate method for nozzle attachment. 150# standard for nozzles; other ratings available.	Wide range of materials available	Flange Sizes: 2" - 12" DN 50 - DN 300
Manifolds	Used to cluster many nozzles into a small physical space	Wide range of materials available	Standard Sizes
			Inlet Outlets
			1/2" x (7) 3/8"-24 UNF
			3/4" x (6) 1/4" or 3/8"
- 16			1" x (6) 3/8" or 1/2"
	www.BETE.co	m	

CALL 413-772-0846 Call for the name of your nearest BETE representative.